

# GRAVOPLY® 2



INDOOR PLASTICS

- Badges
- Identification plates
- Interior signage

- *Microthin surface layer*
- *Perfect for small characters and detailed logos*
- *Low glare matte finish*
- *2-ply and 3-ply*

## Specifications

Surface	<b>Matte</b>
Profile engraving depth	<b>.002" (0.1 mm)</b>
Full sheet	<b>24" x 48" (610 mm x 1220 mm)</b>
Half sheet	<b>24" x 24" (610 mm x 610 mm)</b>
Quarter sheet	<b>12" x 24" (305 mm x 610 mm)</b>
Composition	<b>ABS</b>

## Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
Min. temp.		200°F/93°C	Max. temp.

	Surface color	Core color	2-ply		3-ply
			0.8 mm 1/32"	1.6 mm 1/16"	3.2 mm 1/8"
●	white	red		<b>21928</b>	
●	white	azure blue		<b>21908</b>	
●	white	black	21850	<b>21919</b>	
●	red	white	21851	<b>21921</b>	22016
●	yellow	red		<b>21913</b>	
●	yellow	black		<b>21936</b>	
●	azure blue	white	31401	<b>21923</b>	
●	black	white	21849	<b>21917</b>	29732
●	white	burgundy		21874	
●	almond	burgundy		29709	
●	red	yellow		21910	
●	burgundy	white		21932	
●	yellow	blue		21896	
●	apple green	white		21905	
●	pine green	white		21938	
●	pine green	yellow		21916	
●	sky blue	white		21934	
●	sky blue	black		21895	
●	azure blue	yellow		21911	
●	royal blue	white		21907	
●	brown	white		21930	
●	chocolate brown	white		21876	
●	gray	white		21927	
●	gray	black		21915	
●	black	yellow		21940	

**Bold items are value priced!**

# GRAVOPLY® 2



- Badges
- Identification plates
- Interior signage

- Gravoply 2 Gloss has an extra durable scratch resistant glossy cap
- Microthin surface layer
- Perfect for small characters and detailed logos
- Low glare matte finish on woods, granites and tech patterns



**The ultimate in scratch and wear resistance!**

## Gravoply® 2

			2-ply
			1.6 mm
	Surface color	Core color	1/16"
	white	black	23977
	white	red	23981
	yellow	black	23982
	red	white	23978
	emerald green	white	23983
	blue	white	23979
	grey	white	23980
	black	white	23976

## Specifications

Surface	<b>Matte</b>
Profile engraving depth	<b>.002" (0.1 mm)</b>
Full sheet	<b>24" x 48" (610 mm x 1220 mm)</b>
Half sheet	<b>24" x 24" (610 mm x 610 mm)</b>
Quarter sheet	<b>12" x 24" (305 mm x 610 mm)</b>
Composition	<b>ABS</b>

## Capabilities

Interior			Exterior
Shear			Saw
Silk screen			Hot stamp
Scratch resistant			Flexible
Break resistant			UV resistant
Min. temp.		200°F/93°C	Max. temp.

## Gravoply® 2 Woods

			2-ply
			1.6 mm
	Surface color	Core color	1/16"
	satin light walnut	white	21885
	matte american walnut	white	21880
	satin colonial walnut	white	21879

## Gravoply® 2 Naturals

			2-ply
			1.6 mm
	Surface color	Core color	1/16"
	green marble	almond	22026

## Gravoply® 2 Tech Patterns

			2-ply
			1.6 mm
	Surface color	Core color	1/16"
	black pinstripe	white	22019
	silver grid	black	22022