

**RE
AL
ARM**

INDOOR PLASTICS



GRAVOSTRAT[®]



Industrial identification

- Phenolic material
- Low glare finish
- 3-ply
- Resistant to chemicals and solvents
- Non-flammable
- Conforms to USA military specifications ASTM D 709 ES-1, ES-2, ES-3
- Electrically non-conductive and abrasion resistant
- Saw cut
- Interior use

Low glare

	Surface color	Core color	3-ply	
			1.6 mm 1/16"	3.2 mm 1/8"
●	white	black	30635	30636
●	fire red	white	31117	31119
●	black	white	30647	30648
●	yellow	black	30755	30756

Specifications

Surface	Low glare
Profile engraving depth	.012" (0.3 mm)
Full sheet	36" x 48" (914 mm x 1220 mm)
Half sheet	18" x 48" (457 mm x 1220 mm)
Quarter sheet	18" x 24" (457 mm x 610 mm)
Composition	Rigid thermoset material

Capabilities

	Interior		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■		Flexible
Break resistant			UV resistant
Min. temp.	30°F/0°C	200°F/93°C	Max. temp.

Note: 18" x 48" (457mm x 1220mm) or smaller ships UPS. 36" x 48" (914 mm x 1220 mm) ships via truck.

This material can be engraved but not cut by a laser.